


ACCESORIOS PARA TUBERÍA DE FUNDICIÓN


FITTINGS FOR DUCTILE IRON PIPE


RACCORDS POUR TUYAUTERIE EN FONTE DUCTILE


junta mecánica mechanical joint joint mécanique


BRIDA ENCHUFE FLANGED SOCKET BRIDE À EMBOÎTEMENT			
			
DN	P	L	Kg
80	121	137	11,8
100	121	139	13,3
125	133	145	16
150	135	145	19,7
200	140	152	26,5
250	145	179	37,2
300	160	185	48,7
350	166	192	63
400	168	197	74,3
450	184	203	104,4
500	188	208	128,2
600	205	220	176

CODO DOBLE ENCHUFE DOUBLE SOCKET BEND COUDE DOUBLE EMBOÎTEMENT 11° 15'			
			
DN	P	T	Kg
80	90	30	17,7
100	92	30	19,8
125	95	35	23,8
150	98	35	28,9
200	104	40	39,2
250	104	50	50,8
300	105	55	65,5
350	108	60	78,5
400	110	65	92,5
450	113	70	128,3
500	115	75	153,3
600	120	85	202,1

CODO DOBLE ENCHUFE DOUBLE SOCKET BEND COUDE DOUBLE EMBOÎTEMENT 22° 30'			
			
DN	P	T	Kg
80	90	40	17,1
100	92	40	19,2
125	95	50	22,9
150	98	55	28,1
200	104	65	37,8
250	104	75	53,4
300	105	85	69,5
350	108	95	84,2
400	110	110	101,4
450	113	120	140
500	115	130	168,4
600	120	150	225,6


MANGUITO DOBLE ENCHUFE COLLAR MANCHON			
			
DN	P	L	Kg
80	90	301	17,8
100	92	305	19,9
125	95	316	23,4
150	98	322	28,2
200	104	339	37,3
250	104	338	51,4
300	105	343	65,8
350	108	346	78,6
400	110	355	91,2
450	113	366	125,8
500	115	373	149,4
600	120	387	194,6

CODO DOBLE ENCHUFE DOUBLE SOCKET BEND COUDE DOUBLE EMBOÎTEMENT 45°			
			
DN	P	T	Kg
80	90	55	17,3
100	92	65	19,9
125	95	75	23,8
150	98	85	29,6
200	104	110	41,1
250	104	130	58,6
300	105	150	77,4
350	108	175	96,3
400	110	195	117
450	113	220	161,7
500	115	240	196,3
600	120	285	270,9

CODO DOBLE ENCHUFE DOUBLE SOCKET BEND COUDE DOUBLE EMBOÎTEMENT 90°			
			
DN	P	T	Kg
80	90	100	18,2
100	92	120	21,1
125	95	145	25,8
150	98	170	32,5
200	104	220	46,7
250	104	270	68,1
300	105	320	92,3
350	108	370	117,4
400	110	420	146,4
450	113	470	200,5
500	115	520	247,3
600	120	620	351,4

Dimensiones en mm.
Dimensions in mm.
Dimensions en mm.

TE DOBLE ENCHUFE DERIVACIÓN BRIDA					
DOUBLE SOCKET TEE WITH FLANGED BRANCH					
TÉE DOUBLE EMBOÎTEMENT DÉRIVATION BRIDE					
DN	dn	P	H	L	Kg
80	40	90	155	325	20,4
	60	90	160	325	21,2
	80	90	165	325	22,2
100	60	92	170	349	23,9
	65	92	170	349	23,9
	80	92	175	349	24,8
	100	92	180	349	25,8
125	60	95	190	335	29,5
	65	95	190	335	29,5
	80	95	190	360	28,6
	100	95	195	395	30,3
	125	95	200	395	31,9
150	60	98	200	366	33
	65	98	200	366	33
	80	98	205	366	33,9
	100	98	210	426	36,6
	125	98	215	426	38,1
	150	98	220	426	40,1
	200	104	260	503	57,1
200	60	104	230	383	43
	65	104	230	383	43
	80	104	235	383	43,9
	100	104	240	413	46,1
	150	104	250	503	53,1
	200	104	260	503	57,1
250	80	104	265	383	59
	100	104	270	383	59,8
	150	104	280	448	66,7
	200	104	290	563	76,6
	250	104	300	563	82,4
300	80	105	295	390	74,7
	100	105	300	390	75,5
	150	105	310	445	82,6
	200	105	320	570	94,8
	250	105	330	570	100,4
	300	105	340	645	111,9
350	80	108	325	396	88,5
	100	108	330	396	89,4
	150	108	340	461	97,8
	200	108	350	576	110,8
	250	108	360	576	115,7
	350	108	380	696	140,4




Continuación. Continue.					
DN	dn	P	H	L	Kg
400	80	110	355	385	100,6
	100	110	360	440	107
	150	110	370	530	119,5
	200	110	380	530	123,1
	250	110	390	640	139,6
	300	110	400	640	145,6
	400	110	420	760	174,1
450	100	113	390	476	147,3
	150	113	400	476	150,6
	200	113	410	596	168,6
	250	113	420	596	173,8
	300	113	430	711	193,6
	400	113	450	826	223,2
	450	113	460	826	234,2
500	80	115	415	405	161,8
	100	115	420	485	174
	150	115	430	485	177,3
	200	115	440	600	197
	250	115	450	600	202,3
	300	115	460	715	224,2
	400	115	480	830	255,7
600	500	115	500	890	290
	80	120	475	420	210
	100	120	480	500	225,7
	150	120	490	500	233,1
	200	120	500	615	253,8
	300	120	520	730	285,8
	400	120	540	850	322,8
600	600	120	580	1.020	413,4

JUNTA DE DESMONTAJE

DISMANTLING SLEEVE

JOINT DE DEMONTAGE



DN	A	L	Kg
80	137	208	11,7
100	138	209	13,4
125	172	211	16,1
150	192	234	20,6
200	213	259	29
250	204	254	39,6
300	223	278	51,9
350	247	308	67,3
400	278	340	83,6
450	296	363	111,9
500	327	398	140,5
600	345	426	191,8

